



BZ4920 defoamer additive

Composition: silicone-free organic polymers

Appearance: yellow transparent liquid

Active ingredient: 100%

Application scope: solvent-based coatings, light-curing coatings, solvent-free coatings, printing inks, etc..

Recommended dosage: 0.3-1.0% of the total formula (please test the most appropriate amount before use)

Pre-dilution with recommended solvents will facilitate the addition and mixing, can be added at the grinding stage or paint mixing stage, stirred before use, can be added in the varnish formulation.

Characteristics and advantages:

1. Good compatibility, suitable for high viscosity and high solid coatings, light curing coatings defoamer.
2. It can inhibit the generation of micro-bubbles in coatings, and eliminate the air bubbles generated by coatings in manufacturing and stirring construction.
3. Suitable for shower coating, roller coating and spraying, high defoaming efficiency, high phase solubility, suitable for varnish and color paint, good recoatability, does not contain organic silicon.

Package: 25KG non-recycled blue drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Precautions: Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.