



BZ-5300 general purpose defoamer additive

Composition: modified silicone compounds

Appearance: colorless transparent to slightly yellow liquid

Nonvolatile content: 0.6%

Solvent: Xylene, Tetramethylbenzene

Application scope: solvent-based coatings, light-curing coatings, solvent-free coatings.

Recommended dosage: 0.1-0.8% of the total formula (please test the most appropriate amount before use)

Directions:

In order to obtain sufficient defoaming effect, it is recommended to add it before grinding. If added later, it should be mixed under high enough shear force to ensure good distribution of defoamer.

Characteristics and advantages:

1. It has excellent defoaming and foam inhibition effect, which can inhibit and eliminate the air bubbles generated in the process of coating production, canning and construction, and prevent the generation of pinholes and so on.
2. Good compatibility with various resin systems, especially suitable for medium and high level varnish systems.

Package:

25KG non-recycled blue plastic drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Precautions: Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.