



## BZ-6800A Epoxy defoamer additive

**Composition:** Modified Silicone Foam Breaking Polymers

**Appearance:** Milky white liquid

**Active ingredient:** 100%

**Application scope:** solvent-based coatings; light-curing coatings, solvent-free coatings.

**Recommended dosage:** 0.1-1.0% of the total formula (please test the most appropriate amount before use)

In order to obtain sufficient defoaming effect, it is recommended to add it before grinding. If it is added later, it should be mixed under high enough shear force to ensure the defoaming effect.

### **Characteristics and advantages:**

- 1、 It has excellent defoaming and foam inhibition effect, it can inhibit and eliminate the air bubbles generated in the process of production, canning and construction of ink, especially for the elimination of air bubbles in high viscosity ink in a significant effect.
- 2、 Used in epoxy system, it has good foam inhibition effect on epoxy roll coating.

**Package:** 25KG non-recycled blue barrel.

The product is not completely empty before use, after use must be covered tightly.

**Storage:** Keep away from heat and light source, and keep away from light.

**Precautions:** Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company has the right to improve its own products, any changes in its specifications, without prior notice.