



BZ-066N Special Organic Silicon Antifoam additive

Composition: Fluorine modified siloxane

Appearance: colorless to yellowish transparent liquid

Non-volatile content: 2.0%

Solvent: Xylene

Application scope: solvent-based coatings, light-curing coatings, solvent-free coatings.

Recommended dosage: 0.05-0.5% of the total amount of formula (please test the most appropriate amount before use)

Directions for use:

In order to obtain sufficient defoaming effect, it is recommended to add it before grinding. If added later, it should be mixed under high enough shear to ensure good distribution of defoamer.

Characteristics and advantages:

- 1、 It has high efficient defoaming and foam inhibition performance, and it has very high defoaming effect on the microfoam in the coating products.
- 2, especially for white top coat and color paint defoaming effect is good, for UV roller coating mechanical bubble elimination has good effect.

Package:

25KG non-recycled blue drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Precautions: Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.