



BZ-401 Organosilicon defoamer additive

Composition: Modified silicone compounds

Typical physical data

Appearance: transparent colorless to slightly yellow liquid

Active ingredient: 1%

Solvent: Xylene, Butyl ester

Application scope: Suitable for: solvent-borne coatings; recommended for: light-curing coatings, solvent-free coatings.

Recommended dosage: 0.1-1.0% of the total formula (please test the most appropriate dosage before use).

Dosage: In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, it should be mixed under high enough shear force to ensure good distribution of defoamer.

Characteristics and advantages:

Good compatibility with various resin systems, with excellent defoaming and bubble-breaking effect, can eliminate the bubbles generated during the production, canning and construction of coatings, especially for the two-component coating reaction bubbles generated by the defoaming effect is extremely significant, to prevent the generation of pinholes and so on.

Packing:

25KG non-recycled blue pail.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Precautions: Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.