



BZ-404D High solid acrylic defoamer additive

Composition: Pure acrylate polymer

Appearance: colorless to light yellow transparent liquid

Active ingredient: $\geq 80\%$.

Solvent: trimethylbenzene

Application scope: solvent-borne coatings; light-curing coatings, solvent-free coatings.

Recommended dosage: 0.1-0.5% of the total formula (please test the most appropriate dosage before use).

Dosage: In order to obtain sufficient defoaming effect, it is recommended to add it before grinding. If added later, it should be mixed under high enough shear force to ensure the defoaming effect.

Characteristics and advantages:

It has excellent defoaming and foam inhibition effect, which can inhibit and eliminate the bubbles generated during the production, canning and construction of coatings, especially for the bubbles generated by the reaction of two-component coatings, and the defoaming effect is extremely significant.

This kind of defoamer, does not affect the recoating and adhesion, will not produce shrinkage, etc..

Package: 25KG/180kg non-recycled blue drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light sources and keep away from light.

Precautions: Please carefully evaluate the effect on phase solubility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.