



## BZ-406 Ink defoamer additive

**Composition:** Special modified siloxane

**Appearance:** milky white turbid liquid

**Active ingredient:** 100%

**Solvent:** None

**Application scope:** solvent-based coatings; light-curing coatings, solvent-free coatings.

**Recommended dosage:** 0.1-1.0% of the total formula (please test the most appropriate dosage before use).

**Dosage:** In order to obtain sufficient defoaming effect, it is recommended to add it before grinding. If added later, it should be mixed under high enough shear force to ensure the defoaming effect.

**Characteristics and advantages:**

1, has excellent defoaming, foam inhibition effect, can inhibit and eliminate the ink in the production, canning, construction process of air bubbles, especially for high-viscosity ink bubble elimination in the remarkable effect of ink high-speed printing has a very good effect of foam inhibition.

2, Used in epoxy system, it has good foam inhibition effect on epoxy roll coating.

**Package:** 25kg non-recycled blue plastic drum.

Before the product is completely empty, the lid must be tightly closed after use.

**Storage:** Keep away from heat and light sources and keep away from light.

**Caution:** Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.