



BZ-411B defoamer additive

Composition: Modified silicone compounds

Appearance: colorless to yellowish transparent liquid

Nonvolatile content: 2.0%

Solvent: Xylene, Cyclohexanone

Application scope: solvent-borne coatings, light-curing coatings, solvent-free coatings.

Recommended dosage: 0.1-1.0% of the total formula (please test the most appropriate dosage before use).

Dosage: In order to obtain sufficient defoaming effect, it is recommended to add before grinding. If added later, it should be mixed under high enough shear force to ensure good distribution of defoamer.

Characteristics and advantages:

- 1, BZ411B has better compatibility than BZ410 in all kinds of resin systems, with excellent defoaming and foam inhibition effect, and has very high defoaming effect on the microfoam in coating products.
- 2, with other types of defoamers can not be compared with the compatibility, especially for medium and high polarity varnish, matte paint, white top coat, PE series.

Package:

25KG non-recycled blue pail.

Cover tightly after use before the product is completely empty.

Storage: Keep away from heat and light sources and keep away from light.

Caution: Please carefully evaluate the effect on compatibility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company has the right to improve its own products, any changes in its specifications, without prior notice.